

ELECTRICAL INPUT CHOOSE (ONE OF THE FOLLOWING) :

WATER INLET:

-3/8" MALE FLARE, 20 TO 75  
PSIG, 2 GPM MIN FLOW RATE.

TOTAL WEIGHT  
IN USE (LB/KG):  
414/191.6

- 120/208-240VAC 1PH 3 WIRE+GRD 6.9-9.1KW 33.3-38.3 A
- 120/208-240VAC 1PH 3 WIRE+GRD 9.1-12.1 KW 44.1-50.8 A
- 120/208-240VAC 3PH 4 WIRE+GRD -6.9-9.1 KW 19.5-22.4 A
- 120/208-240VAC 3PH 4 WIRE+GRD -9.1-12.1KW 25.8-29.7 A
- 120/208-240VAC 3PH 4 WIRE+GRD -13.6-18.1KW 38.3-44.1 A
- 120/208-240VAC 3PH 4 WIRE+GRD -18.1-24.1KW 50.8-58.5 A

STEAM: 120VAC 1PH 2WIRE+GRD 2A  
80LBS PER HOUR MAX. 10-15 PSI.  
EXPORT VOLTAGES ARE ALSO AVAILABLE.

CHECK ELECTRICAL SPECIFICATION LABEL FOR SPECIFIC SERVICE REQUIRED.  
UTILITIES CONNECTIONS THROUGH BOTTOM AND/OR BACK WALL OF UNIT.

ELECTRIC INPUT AND WATER CONNECTION  
FROM REAR

