

CBS-2132XTS SKU #	Wiring Diagram
E213254	1401.00085.00
E213262	1401.00078.00
E213263	1401.00078.00
E213264	1401.00078.00
E213265	1401.00078.00
E213266	1401.00078.00
E213267	1401.00078.00
E213268	1401.00078.00
E213269	1401.00078.00
E213280	1401.00050.00
E213281	1401.00050.00
E213290	1401.00085.00
E213291	1401.00085.00
E213292	1401.00085.00

North America & International CBS_2132XTS—Twin 3 liters airpot version Electrical Configurations									
Configuration Codes		Heater Configuration	Voltage	Phase	Wires	Electrical Connection	KW	Maximum Amp Draw	Brew-Volume/Hour (3 liters per batch)
Plastic Brewbasket	Stainless Steel Brewbasket								
E213290	E213290M	2 x 2.3 kW	200-240	1	2+G	Hardwired	3.3-4.7	16.5-19.7	11.5 gal/43.5
E213291	E213291M	2 X 3.0 kW	200-240	1	2+G	Hardwired	4.2-6.1	21.3-25.5	14.3 gal/54 liters

Japan CBS_2132XTS—Twin 3 liters airpot version Electrical Configurations									
Configuration Codes		Heater Configuration	Voltage	Phase	Wires	Electrical Connection	KW	Maximum Amp Draw	Brew-Volume/Hour (3 liters per batch)
Plastic Brewbasket	Stainless Steel Brewbasket								
E213280	E213280M	2 x 2.3 kW	200	1	2+G	Hardwired	3.3	16.3	11.0 gal/42.0
E213281	E213281M	2 X 3.0 kW	200-240	1	2+G	Hardwired	4.2	21.3	14.9 gal/56 liters

CE CBS_2132XTS—Twin 3 liters airpot version Electrical Configurations									
Configuration Codes		Heater Configuration	Voltage	Phase	Wires	Electrical Connection	KW	Maximum Amp Draw	Brew-Volume/Hour (3 liters per batch)
Plastic Brewbasket	Stainless Steel Brewbasket								
E213265	E213265M	2 x 2.3 kW	230/400	2	2L,N,PE	Hardwired	4.3	9.6	11.0 gal/42.0
E213262	E213262M	2 X 3.0 kW	230/400	2	2L,N,PE	Hardwired	5.6	12.4	14.9 gal/56 liters
E213266	E213266M	2 X 3.0 kW	230	1	L,N,PE	Hardwired	5.6	24.4	14.3 gal/54 liters
E213268	E213268M	2 x 2.3 kW	230	1	L,N,PE	Hardwired	4.3	18.8	5.8 gal/22 liters

Has CE and NSF-4 certification. Internal EMI filter. Not cUL or UL listed

North America & International Versions and Japan CBS_2132XTS—Twin 3.8 liters/1 gallon dispenser version Electrical Configurations									
Configuration Codes		Heater Configuration	Voltage	Phase	Wires	Electrical Connection	KW	Maximum Amp Draw	Brew-Volume/Hour (3.8 liters per batch)
Plastic Brewbasket	Stainless Steel Brewbasket								
E213292	E213292M	2 X 3.0 kW	200-240	1	2+G	Hardwired	4.2-6.1	21.3-25.5	14.3 gal/54 liters

CE CBS_2132XTS—Twin 3.8 liters/1 gallon dispenser version Electrical Configurations									
Configuration Codes		Heater Configuration	Voltage	Phase	Wires	Electrical Connection	KW	Maximum Amp Draw	Brew-Volume/Hour (3.8 liters per batch)
Plastic Brewbasket	Stainless Steel Brewbasket								
E213264	E213264M	2 x 2.3 kW	230/400	2	2L,N,PE	Hardwired	4.3	9.6	11.0 gal/42.0 lit
E213263	E213263M	2 X 3.0 kW	230/400	2	2L,N,PE	Hardwired	5.6	12.4	14.9 gal/56 liters
E213267	E213267M	2 X 3.0 kW	230	1	L,N,PE	Hardwired	5.6	24.4	14.3 gal/54 liters
E213269	E213269M	2 x 2.3 kW	230	1	L,N,PE	Hardwired	4.3	18.8	5.8 gal/22 liters

Has CE and NSF-4 certification. Internal EMI filter. Not cUL or UL listed



